

Technical Specifications of Exide Xpress Range of Batteries

BATTERY TYPE	PART NUMBER	CAPACITY (AH) 20HR (REF)	MAXIMUM OVERALL DIMENSIONS			Nominal Filled Weight (KG)	ELECTROLYTE VOLUME (LITRE)	CHARGING CURRENT (A)	CCA AT - 18°C AS PER		ACID LEVEL INDICATOR	BATTERY LAYOUT
			L (MM)	W (MM)	H (MM)				IEC	SAE		
XP800	FXP0-XP800	80	305	173	225	23.0	4.9	5.0	420	530	Present	Right Layout -□□□□+
XP800L	FXP0-XP800L	80	305	173	225	23.0	4.9	5.0	420	530	Present	Left Layout +□□□□-
XP880	FXP0-XP880	88	410	176	233	26.6	6.8	5.5	430	550	Present	Left Layout +□□□□-
XP1000	FXP0-XP1000	100	410	176	233	28.1	6.3	6.5	475	580	Present	Left Layout +□□□□-
XP1100	FXP0-XP1100	110	410	176	233	29.6	6.0	7.0	550	700	Present	Right Layout -□□□□+
XP1300	FXP0-XP1300	130	505	182	257	35.1	8.3	9.0	560	720	Present	Right Layout □□□□:
XP1500	FXP0-XP1500	150	508	222	257	42.0	10.4	9.0	640	785	Present	Right Layout □□□□:
XP1800	FXP0-XP1800	180	521	278	270	55.1	15.9	13.0	830	1050	Present	Right Layout □□□□:
XP2000	FXP0-XP2000	200	521	278	270	56.8	15.5	14.0	910	1150	Present	Right Layout □□□□: